



19" Responder Fast Deployment Oil Containment Boom



What is a 19" Responder Fast Deployment Oil Containment Boom and who is it for?

This Enviro-USA boom is ideal for calm water & light current oil spill applications in protected ports, marinas, bays, harbors, inlets and just about any inland body of water. 19 Inch is the most common size for first response and long term oil spill clean-up. Widely used by contract emergency response companies.

Why use Fast Deployment Oil Containment Booms versus Standard Booms?

Oil containment booms are used in calm water as a first response to an oil spill or by Spill Response Contractors to divert, control and maintain an oil spill. Once the spill has been contained the contractor will then proceed to recover and clean up the oil. The main advantage of using a Fast Deployment boom is the reduced time it takes to deploy thanks to the use of a reel system.

Where are 19" Responder Fast Deployment Oil Containment Booms used?

Calm water and slow current oil spill applications, such as:

- Protected marinas and unprotected in some cases
- Protected ports
- Bays

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM



- Harbors
- Inlets
- Medium & large ponds
- Canals
- Lagoons
- Lakes
- Waterways
- Reservoirs
- Wetlands

Specifications

This Enviro-USA boom is compliant with OPA 90, [US Coast Guard – OSRO and ASTM F1523 Guidelines](#).

- Oil Booms are available in 50 and 100 foot sections or any custom length up to 100’.
- Numerous sections can easily and quickly be connected together.
- Numerous fabrics are available for short or long term deployments.

6” Freeboard & 12” Draft, 22 oz. PVC fabric, ballast chain, ASTM connectors, available with or without a top tension cable.

A top tension cable is required if the boom is going to encounter strong currents, windy conditions or a lot of water movement due to boat and recreational activity nearby.

19” FAST DEPLOYMENT Oil Containment Boom has a flat float, its light weight, does not require inflation, stores and deploys easily from a reel, and a **1,000 ft can be deployed in about 8-10 minutes with minimal personnel** (3-4 persons). This boom is a favorite by Marinas & Protected Ports as it works well for the application and it’s very affordable.

Enviro-USA’s 19” Protected Port FAST DEPLOYMENT Oil Containment Boom has a top tension cable thereby providing greater tensile strength and is most often used for oil spills in protected ports, inlets, harbors, estuaries, unprotected marinas, bays and of course can also be used on all of the above listed applications.

For a specific spec sheet, please call our office at 321-222-9551 or [send us an e-mail](#).

Free Quote

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM



For a quick quote call our manufacturing plant: (321) 222-9551 or fax us your requirements to: (321) 206-4563.

As a manufacturer having spent a lot of time in this industry and being very familiar with oil spills and government requirements for different applications, we strive to manufacture a quality product, appropriate for rough river applications, while keeping cost down to a minimum. "Enviro-USA Guarantees its Quality and the Lowest Price in the USA".

A large, light green, stylized graphic of a drop or splash, positioned in the lower half of the page. It has a thick, curved shape with a white outline, resembling a large drop or a splash of liquid.

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM