



24" Unprotected Port Fast Deployment Oil Containment Boom



What is a 24" Unprotected Port Fast Deployment Oil Containment Boom and who is it for?

This Enviro-USA boom is highly recommended by Port Authorities as the appropriate size for Unprotected Ports due to its bigger float which offers a higher freeboard that will prevent splash over due to windy conditions and choppy water. The primary users are spill response contractors.

Why use Fast Deployment Oil Containment Booms versus Standard Booms?

Oil containment booms are used in choppy waters as a first response to an oil spill or by Spill Response Contractors to divert, control and maintain an oil spill. Once the spill has been contained the contractor will then proceed to recover and clean up the oil. The main advantage of using a Fast Deployment boom is the reduced time it takes to deploy thanks to the use of a reel system.

Where are 24" Unprotected Port Fast Deployment Oil Containment Booms used?

Enviro-USA's 24" Unprotected Port fast deployment oil boom can also be used in:

- Unprotected Marinas
- Harbors
- Gulfs
- Beaches

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM



Specifications

This Enviro-USA boom is compliant with OPA 90, [US Coast Guard – OSRO and ASTM F1523 Guidelines](#).

- Oil Booms are available in 50 and 100 foot sections or any custom length up to 100'.
- Numerous sections can easily and quickly be connected together.
- Numerous fabrics are available for short or long term deployments.

8” Freeboard & 16” Draft, 22 oz. PVC fabric, top tension cable, ballast chain, and ASTM connectors.

Enviro-USA’s 24” FAST DEPLOYMENT oil containment boom is ideal for fast response in unprotected ports as it has a flat float, its light weight, does not require inflation, stores and deploys from a reel thereby occupying less space, less manpower and **1,000 ft can be deployed in 8-10 minutes**. It has a top tension cable which provides great tensile strength, which is required in most ports due to strong currents, tide changes, windy conditions and choppy water. This is a great product for fast deployment.

For a specific spec sheet, please call our office at 321-222-9551 or [send us an e-mail](#).

Free Quote

For a quick quote call our manufacturing plant: (321) 222-9551 or fax us your requirements to: (321) 206-4563.

As a manufacturer having spent a lot of time in this industry and being very familiar with oil spills and government requirements for different applications, we strive to manufacture a quality product, appropriate for rough river applications, while keeping cost down to a minimum. “Enviro-USA Guarantees its Quality and the Lowest Price in the USA”.

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM