



Dewatering Bags and Socks provide a simple, cost-effective solution for removing sediment and silt from discharged water on construction sites, dredging projects, municipalities, and industrial facilities. Manufactured from durable, needle-punched, non-woven standard or heavy-duty geotextile fabric, they allow water to pass through while capturing fine soils and sediment for cleaner discharge.

Standard (8 oz.) and Heavy Duty (10 oz.) Dewatering Bags

Fabric Material: 8 oz. / 10 oz. Non-Woven
Filter Rate: 90 / 75 gpm
Microns: 177 / 149
AOS: 80 / 100 US Sieve

Size

6 ft. x 6 ft. | 10 ft. x 15 ft. | 15 ft. x 15 ft. | 15 ft. x 20 ft. | 15 ft. x 25 ft.

Capacity


1.44 yds³ | 6 yds³ | 9.6 yds³ | 12 yds³ | 15 yds³



Standard (8 oz.) and Heavy Duty (10 oz.) Dewatering Socks

Fabric Material: 8 oz. / 10 oz. Non-Woven
Diameter: 4 in., 6 in., 8 in., 12 in., 16 in.
Length: 60 in.
Filter Rate: 90 / 75 gpm
Microns: 177 / 149
AOS: 80 / 100 US Sieve

- Needle-Punched, Non-Woven Geotextile Fabric
- Quick and Easy Installation Direct to a Discharge Hose or Pipe
- Easy to Ship and Store on Site
- Filters Soils and Particles as Small as 4x the Width of a Human Hair
- Fits 4 - 16 in. Diameter Discharge Hoses
- Can be Implemented as a SWPPP Solution or Stormwater BMP
- Helps Sites Comply with NPDES, 40 CFR 122.26 (1999)



Dewatering Tubes

Dewatering Tubes provide a high-capacity, cost-effective solution for large-scale dewatering, sludge removal, and sediment containment projects. Constructed from durable woven geotextile or composite fabrics, they effectively separate water from solids and are ideal for applications including wastewater treatment, mining, shoreline restoration, construction, industrial sludge management, coal ash ponds, landfills, and environmental remediation.

Diameter	Laydown Length	Tube Volume (yds. ³ /LF)
15 ft.	50 ft., 100 ft., 150 ft., 200 ft.	.06
30 ft.	50 ft., 100 ft., 150 ft., 200 ft.	2.3
45 ft.	50 ft., 100 ft., 150 ft., 200 ft.	4.1
60 ft.	50 ft., 100 ft., 150 ft., 200 ft.	6.2
75 ft.	50 ft., 100 ft., 150 ft., 200 ft.	0.0
90 ft.	50 ft., 100 ft., 150 ft., 200 ft.	0.0

- Made from Weaving Polypropylene Fabric with Superior Tensile Strength Value
- Designed for 24/7 Continuous Operation
- Stackable and Compatible with Multiple Filling Ports
- Reduces Waste Volume and Lowers Material Handling and Disposal Costs
- UV Stabilized

