



52" Inflatable Oil Containment Boom for OPEN SEA



What is a 52" Inflatable Oil Containment Boom for OPEN SEA and who is it for?

This Enviro-USA boom is highly recommended by Port Authorities as the appropriate size for Sea applications.

Why use an Inflatable Oil Containment Boom versus a standard model?

Enviro-USA's inflatable Oil Containment Barriers are perfect if you are limited by storage, must have a quick deployment due to environmental sensitive areas nearby and/or have a tight budget.

Where are 52" Inflatable Oil Containment Booms for used?

Enviro-USA's 52" inflatable oil boom is used mostly for open sea applications including:

- Unprotected and Protected Ports
- Harbors
- Gulfs
- Beaches
- Shoreline
- Offshore

Specifications

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM



This Enviro-USA boom is compliant with OPA 90, [US Coast Guard – OSRO and ASTM F1523 Guidelines](#).

Enviro-USA's inflatable booms offer:

- High buoyancy to weight ratio which provides excellent wave adapting capability and heave response.
- Individual air chambers which provides dependability, integrity and peace of mind.
- Large diameter air chambers which provide plenty of water plane surface allowing the boom to maintain a maximum freeboard at all times.

Options:

- Oil Booms are available in 50 and 100 foot sections or any custom length up to 100'.
- Numerous sections can easily and quickly be connected together.
- Numerous fabrics are available for short or long term deployments.

“Compliant with OPA 90, US Coast Guard – OSRO and ASTM F1523 Guidelines”

21” Freeboard & 28” Draft, Heavy Duty 41 oz. orange fabric, **3” fin above air chambers**, ballast chain, and ASTM connectors.

The freeboard & draft are perfect in size for this type of application. The 21” air chambers and 3” fin above the air chambers increase protection and prevent splash over due to waves breaking, windy conditions and/or choppy water. This boom is lightweight and it can easily be stored, deployed and retrieved from a hydraulic reel with minimal manpower. **1,000 ft (300m) can be deployed in approximately 13 minutes with only 3 persons.** It is the perfect inflatable boom for responding to oil spills in open sea applications.

For a specific spec sheet, please call our office at 321-222-9551 or [send us an e-mail](#).

Free Quote

For a quick quote call our manufacturing plant: (321) 222-9551 or fax us your requirements to: (321) 206-4563.

As a manufacturer having spent a lot of time in this industry and being very familiar with oil spills and government requirements for different applications, we strive to manufacture a quality product,

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM



appropriate for offshore applications, while keeping cost down to a minimum. “Enviro-USA Guarantees its Quality and the Lowest Price in the USA”.

A large, light green, stylized graphic of a drop or splash, composed of several overlapping curved bands, is positioned in the lower half of the page.

3855 N. Highway 1, Cocoa, FL 32926
Tel: (321) 222-9551, Fax: (321) 206-4563

WWW.ENVIRO-USA.COM